

Generator 6.5 kva

GENERATOR SPECIFICATION		ENGINE SPECIFICATION	
Voltage	230/115	Engine	Honda GX390
Phase	1	Emissions certified	EU Stage V
Frequency	50Hz	Cylinders	Single
Prime Power (PRP)	6.5kVA / 5.2kW	Distribution	O.H.V.
Alternator	NSM C100 SG	Aspiration	Naturally aspirated
Alternator Type	Brushless - Smooth Waveform	Cooling	Air
Fuel tank capacity	15.5 Litres	Displacement	389 cm ³
Autonomy 75% load	6.2 Hours	Rpm	3000
LWA	97	Starting system	Recoil
dBA @ 7M	72	Fuel	Unleaded 86 octane or higher



DIMENSIONS (mm)			WEIGHT (KG)
Length	Width	Height	77
710	510	600	



CONTROL BOX	STANDARD FEATURES
<ul style="list-style-type: none"> ▪ 115V: 1 x 16A & 1 x 32A BS4343 sockets. ▪ 230V: 1 x 16A & 1 x 32A BS4343 sockets. ▪ Reset circuit breaker overload protection. ▪ Voltage selector switch. 	<ul style="list-style-type: none"> ▪ Oil alert/low oil shutdown. ▪ 3 Year engine warranty (Limited). ▪ Full wrap-around frame. ▪ Brushless smooth waveform alternator. ▪ Long run fuel tank.
OPTIONS	POWER DEFINITION
<ul style="list-style-type: none"> ▪ AVR (Automatic Voltage Regulator). ▪ Electric start. ▪ Long run tank. ▪ Single voltage. ▪ Trolley kit. ▪ 3 Phase version. 	<p>Prime Power (PRP) : Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1 under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.</p>

+44 (0) 1933 677911

www.stephill-generators.co.uk





Made in Britain

HONDA

Legendary Honda
engineering



Versatile electrical
supply outputs



Powerful Honda
GX390 engine



Fully welded wrap
around carry frame



15.5 L fuel tank - 6.2 hours
run time at 75% load

Generator 2.7 kva

GENERATOR SPECIFICATION		ENGINE SPECIFICATION	
Voltage	230/115	Engine	Honda GX160
Phase	1	Emissions certified	EU Stage V
Frequency	50Hz	Cylinders	Single
Prime Power (PRP)	2.7 kVA / 2.2 kW	Distribution	O.H.V.
Alternator	NSM K100C	Aspiration	Naturally aspirated
Alternator Type	Brushless - Smooth Waveform	Cooling	Air
Fuel tank capacity	3.1 Litres	Displacement	163 cm ³
Autonomy 75% load	3.1 Hours	Rpm	3000
LWA	94	Starting system	Recoil
dBA @ 7M	69	Fuel	Unleaded 86 octane or higher



DIMENSIONS (mm)			WEIGHT (KG)
Length	Width	Height	
610	420	415	41



CONTROL BOX	STANDARD FEATURES
<ul style="list-style-type: none"> ▪ 1 x 16A 230V & 1 x 16A 115V BS4343 sockets. ▪ Reset circuit breaker overload protection. ▪ Voltage selector switch. 	<ul style="list-style-type: none"> ▪ Oil alert/low oil shutdown. ▪ 3 Year engine warranty (Limited). ▪ Full wrap-around frame. ▪ Brushless smooth waveform alternator.